www.HexadyneGroup.com





-

HEXADYNE CORPORATION 361 Van Ness Way, Ste 303 Torrance, CA 90501



inforequest@hexadynegroup.com

ROBINSON



Copyright 2013 Robinson Armament Co. All Rights Reserved

STANDARD



Specifications

- **Operation:** Adjustable Gas, Piston Driven, Heavy Duty 3-Lug Rotating Bolt
 - Length: 33" Overall with 16" Barrel 27" Overall with Stock Folded
- Rail Length:17" Full Top Rail8" Side & Bottom Rail
 - Weight: 7.5lbs Empty
- Barrel Lengths: 11", 12", 14.7", 16" and 18.6" in both Heavy and Light contours
 - Calibers: 5.56 NATO, 6.8 SPC, 7.62x39. 5.45x39, 6.5 and others in development
 - **Colors:** Black, FDE, OD and others upon request

The "Standard" configuration represents the ultimate battle rifle. The ambidextrous ergonomic controls allow the operator to keep his eyes on the target while manipulating the controls with either hand. Not only is the XCR[®] super reliable and durable, its maintenance is extremely simple, lowering the total cost of ownership.

> Specifications subject to change. Patented and Patents pending.

Specifications

- **Operation:** Adjustable Gas, Piston Driven, Heavy Duty 3-Lug Rotating Bolt
 - Length: 27" Overall with 10" Barrel 21" Overall with Stock Folded
- Rail Length:15.25" Full Top Rail6.25" Side & Bottom Rail
 - Weight: 6.5lbs Empty
- **Barrel Lengths:** 10" on both Heavy and Light contours
 - Calibers: 5.56 NATO, 6.8 SPC, 7.62x39. 5.45x39, 6.5 and others in development
 - **Colors:** Black, FDE, OD and others upon request

The "Mini" configuration is ideal for use as a CQC (close quarters combat) weapon or as an entry weapon for law enforcement. Despite its small size, the Mini has the ability to fire full powered rifle cartridges accurately up to at least 200 yards with a 10" barrel.

Note: The XCR "Mini" is an NFA firearm requiring special registration for lawful possession. ALL NFA RULES APPLY

Specifications subject to change. Patented and Patents pending.





www.HexadyneGroup.com



MICRO



Specifications

Operation: Adjustable Gas, Piston Driven, Heavy Duty 3-Lug Rotating Bolt

- Length: 25" Overall with 7.5" Barrel 18" Overall Folded
- Rail Length:13.25" Full Top Rail4.25" Side & Bottom Rail

Weight: 6.2lbs Empty

Barrel7.5" (Standard & Mini barrelsLengths:are compatible, though gas
system is visible)

Calibers: 5.56 NATO, 6.8 SPC, 7.62x39. 5.45x39, .300 BLK and others in development

Colors: Black, FDE, OD and others upon request

Note: The XCR "Micro" is an NFA firearm requiring special registration for lawful possession.

ALL NFA RULES APPLY The "Micro" configuration is ideal for diplomatic protection or deploying from vehicles or other confined spaces. A shorter stock and shorter barrel allow the Micro to fit in smaller spaces either cased or slung. Despite its size, the Micro has the ability to fire full powered rifle cartridges up to at least 100 yards with a 7.5" barrel

Specifications subject to change. Patented and Patents pending.

Specifications

Operation:	Adjustable Gas, Piston Driven, Heavy Duty 3-Lug Rotating Bolt
Length:	18.5" Overall with 7.5" Barrel on Micro Upper 21" Overall with 10" Barrel on Mini Upper
Rail Length:	13.25" Full Top Rail 4.25" Side & Bottom Rail
Weight:	5.2lbs Empty
Barrel Lengths:	7.5" on Micro Upper 10" on Mini Upper
Calibers:	5.56 NATO, 6.8 SPC, 7.62x39. 5.45x39, 6.5 and others in development
Colors:	Black, FDE, OD and others upon request
auto-loading pis rifle cartridges. weapon or as a backpacking. A	ol" is one of the most compact stols capable of firing full powered It is ideal as a personal defense compact high powered pistol for plate on the back of the receiver ling swivel. We also offer pistols

PBIO

Specifications subject to change. Patented and Patents pending.

based on the Mini platform with 10" barrels.



www.HexadyneGroup.com

FEATURES



Compatible with Industry Standard M-16 type Magazines, Grips and Sights.

All controls are located so that they can be manipulated quickly with either hand without taking your eyes off target.

INNOVATIONS

- 1. Piston driven adjustable gas system
- 2. Ambidextrous bolt release
- 3. Ambidextrous magazine release
- 4. Ambidextrous short throw paddle safety
- 5. Single button breakdown for cleaning
- 6. Standard fully integrated 1913 rail system
- 7. Left side non-reciprocating charging handle with integrated forward assist
- 8. New Fully Adjustable (FAST) stock system with double locking hinge and quick deployment button
- 9. Heavy duty bolt, extractor and ejector
- 10. Quick change barrel locking mechanism Two-position adjustable cheek piece

11

12

11. All metal stock (except for the cheek piece and butt pad)

For more information visit

www.HexadyneGroup.com

Hexadyne Corporation 361 Van Ness Way, Ste 303 Torrance, CA 90501

TEL (310) 320-9783 FAX (310) 320-0172

INNOVATIONS

STANDARD

XCR-M

Specifications

- **Operation:** Adjustable Gas, Piston Driven, Heavy Duty 3-Lug Rotating Bolt
 - Length: 38" Overall with 18.6" Barrel 31" Overall with Stock Folded
- Rail Length: 20" Full Top Rail 9.5" Side & Bottom Rail
 - Weight: 9.25lbs Empty with 18.6" Barrel Empty
 - Barrel 16", 18.6" & 20" in both heavy & Lengths: light contours
 - Calibers: 7.62 NATO, .260 Rem and others in development
 - Colors: Black, FDE, OD and others upon request

The "Standard" XCR-M is the ideal full powered combat rifle. Like it's smaller brother, the XCR-L, the XCR-M has the same ergonomic controls allowing the operator to keep his eyes on target while manipulating all controls with either hand. Only a barrel is needed to change calibers since all rounds used are based on the .308 cartridge.

> Specifications subject to change. Patented and Patents pending.

Specifications

- Adjustable Gas, Piston Operation: Driven, Heavy Duty 3-Lug Rotating Bolt
 - Length: 31" Overall with 13" Barrel 25" Overall with Stock Folded
- Rail Length: 18.5" Full Top Rail 8" Side & Bottom Rail
 - Weight: 8lbs Empty with 13" Barrel Empty
 - Barrel 13", 14.7" & 16" Lengths: in both heavy & light contours
 - Calibers: 7.62 NATO, .260 Rem and others in development
 - Colors: Black, FDE, OD and others upon request

The XCR-M in "Mini" configuration uses a shorter upper receiver and can accept shorter barrels. Using a 13" or 16" barrel, the rifle is not much heavier than many 5.56 Rifles. The light weight combined with extremely low recoil make the XCR-M Mini the perfect patrol rifle. This rifle is a "Must Have" for the serious professional.

Specifications subject to change. Patented and Patents pending.



www.HexadyneGroup.com

www.HexadyneGroup.com

CALIBER KITS



Calibers & 5.56 NATO: 1/9 twist available **Twists** for 16", 14.7", and 18.6". 1/7 twist available for 7.5", 10", 11", 12", 14.7", 16" and 18.6"

> 6.8 Remington: 1/11 twist available for 7.5", 10", 14.7", 16" and 18.6". Spec II Chamber used.

7.62x39: 1/10 twist available in 7.5", 10", 14.7", 16" and 18.6".

5.45x39: 1/8 twist available in 7.5", 10", 14.7" and 16"

6.5: 1/8 twist available in 14.7", 16" and 18.6"

.300 BLK: 1/8 twist available in 7.5", 9" and 10"

.308: 1/10 twist available in 13", 14.7", 16", 18.6" and 20".

.260: 1/8 twist available in 13", 14.7", 16", 18.6", and 20"

Magazines 5.56, .300 BLK use standard M1-6, magazines, available in 5, 10, and 30 round capacities.

> 6.8 and 6.5 use special M-16 type magazines, available in 5, 10, and 25 round capacities

7.62x39 uses special M-16 type magazines. Available in 5, 10, and 30 Round Capacities.

.308 and .260 use standard SR-25 type magazines. Available in 5, 10, and 20 round capacities

Specifications

Materials:	All metallic except Cheek Rest and Butt Pad.
Length of Pull:	On XCR-L: 10" to 13" in .5" increments. On XCR-M: 10.5" to 13.5" in .5" increments
Height Adjustment:	Cheek Rest: 2 positions in .25" increments; Stock body: 3 positions in .25" increments.
Hinge:	Made from Steel. Locks in deployed and folded positions. Contains QD sling swivel mounting hole.
ompatability:	Fits all XCR-L and XCR-M Rifles regardless of

Compatability: Fits all XCR-L and XCR-M Rifles regardless of manufacturing date.



FAST STOCK

Specifications subject to change. Patented and Patents pending.

www.HexadyneGroup.com

www.HexadyneGroup.com